

- COMBINATION LADDERS
- STEP LADDERS
- EXTENSION LADDERS
- MULTI-PURPOSE LADDERS
- CAGES



CONQUEST™



300 LBS RATED | TYPE IA | OSHA + ANSI COMPLIANT

Access a variety of workspaces with the Little Giant® Conquest™ ladder. This versatile, multi-position ladder will help you get stuff done.

1. CARRYING HANDLE

Attached carrying handle improves ladder portability.

2. NARROW ACCESS

Narrow top/back section allows for easier access to roofs, attics and tight spaces.

3. NON-CONDUCTIVE FIBERGLASS

Non-conductive, Hi-Viz green fiberglass rails rated to hold up to 300 lbs.

4. ACCESSORY PORTS

Ports accept various Little Giant accessories to maximize the use of your ladder.

5. RAPID LOCK® FASTENERS

Quickly adjust and configure your ladder.

6. V-BAR AND CORNER FEET

Non-marring, heavy duty v-bar grips poles. New specialized corner feet allow leaning on inside corners.

7. WIDE-FLARED BASE

Feel safe with a solid foundation, increasing side-tip stability.

8. TIP & GLIDE™ WHEELS

Easily move the ladder across the job site with Tip & Glide™ wheels.



DID YOU KNOW?

This multi-position ladder adjusts to a variety of configurations and also has a carrying handle for ease of use.

CARRYING HANDLE

Attached carrying handle improves ladder portability.

V-BAR AND CORNER FEET

Non-marring, heavy duty v-bar grips poles. Specialized corner feet allow for leaning on inside corners.

| PART NUMBER | MODEL | MAX REACH* | STEPLADDER SIZE MIN-MAX | STEPLADDER HIGHEST STANDING LEVEL MIN-MAX | EXTENSION SIZE MIN-MAX | EXT. HIGHEST STANDING LEVEL MIN-MAX | STORAGE HEIGHT | STORAGE DEPTH | WEIGHT |
|-------------|-------|------------|-------------------------|---|------------------------|-------------------------------------|----------------|---------------|----------|
| 17117-001 | 17 | 18' 1" | 4' 6" - 7' 6" | 1' 11.5" - 4' 10" | 9' - 15' | 5' 9" - 11' 7" | 4' 7" | 10" | 37.5 lbs |
| 17122-001 | 22 | 22' | 5' 6" - 9' 6" | 2' 11" - 6' 8" | 11' - 19' | 7' 10" - 15' 6" | 5' 7" | 10" | 46 lbs |

* A 5' 6" PERSON WITH A 12" VERTICAL REACH