



**FLUORESCENT PAINT**

MSDS No.:5770, 5780 Series

MSDS Preparation Date: April 1, 2012

Page 1 of 12

## MATERIAL SAFETY DATA SHEET

### SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

**Product Name** : **FLUORESCENT PAINT**  
 Fluorescent - White (No. 5779)  
 Fluorescent - Red (No. 5780)  
 Fluorescent - Yellow (No. 5782)  
 Fluorescent - Green (No. 5783)  
 Fluorescent - Blue (No. 5784)  
 Fluorescent - Invisible Blue (No. 5785)  
 Fluorescent - Pink (No. 5786)  
 Fluorescent - Gold (No. 5787)

**Product Use** : Paint  
**Chemical Family** : Mixture

**Supplier's name and address:**

**Rosco Laboratories Inc.**

52 Harbor View Avenue  
 Stamford, CT, United States  
 06902

**24 Hr. Emergency Tel #** : (800) 424-9300

**HMIS Rating** : \*- Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

*Health:* 1      *Flammability:* 0      *Reactivity:* 0

**WHMIS Classes:**



TOXIC

### SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredients</u>	<u>CAS #</u>	<u>% (weight)</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
			<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
None reported	N/Av	N/Av	N/Av	N/Av	N/Av	N/Av

### SECTION 3 - HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

Clear liquid. Invisible Blue, No. 5785: Milky, white liquid. May cause skin and eye irritation. No special hazards exist with this product. As with any chemical substance, caution and care will prevent unnecessary accidents and safety problems. Read instructions on label before use.

#### \*\*\*POTENTIAL HEALTH EFFECTS\*\*\*

**Target organs** : None reported by the manufacturer.  
**Routes of exposure** : *Inhalation:* YES    *Skin Absorption:* YES    *Skin & Eyes:* YES    *Ingestion:* YES  
**Potential acute health effects** :

*Eyes:* Causes eye irritation. May cause conjunctivitis, irritation, and inflammation of mucous membranes. May cause burning sensation, redness and tearing (watering). Possible severe irritation.



**FLUORESCENT PAINT**

MSDS No.:5770, 5780 Series

MSDS Preparation Date: April 1, 2012

Page 2 of 12

*Skin:* Irritating to skin. Possible irritation, defatting or dermatitis (rash). Components of the product may be absorbed into the body through the skin. May cause central nervous system depression.

*Inhalation:* Can cause irritation of the respiratory tract. Prolonged exposure to vapors may be harmful to health. If higher concentrations are inhaled, additional symptoms may include coughing, shortness of breath, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. May cause mucous membrane irritation. Other adverse effects: Asphyxia. Severe lung irritation or lung damage, loss of appetite. Sanding and grinding dusts may be harmful if inhaled. Contains particles which may cause lung damage if inhaled in large quantities.

*Ingestion:* Lung aspiration hazard. This product may be aspirated (inhaled) into the lungs during ingestion. May cause lung inflammation. May cause mucous membrane irritation. Ingestion may cause symptoms similar to inhalation. May cause gastrointestinal irritation. Gastrointestinal irritation may include abdominal pain, nausea, diarrhea and vomiting. Other adverse effects : intoxication.

**Potential chronic health effects**

: Prolonged skin contact may defat the skin and produce dermatitis. Harmful by skin absorption. May cause central nervous system depression. Prolonged inhalation of vapors may cause lung damage, including chronic bronchitis.

**Medical conditions aggravated by overexposure**

: None expected, when used as intended.

**Additional health hazards**

: None reported by the manufacturer.

**Potential environmental effects**

: None reported by the manufacturer.

**SECTION 4 - FIRST AID MEASURES**

- Inhalation** : If breathed in, move person into fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Seek immediate medical attention/advice.
- Skin contact** : Flush with plenty of water. Wash off with soap and plenty of water. Remove and wash contaminated clothing before re-use. If irritation persists, seek prompt medical attention.
- Eye contact** : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If irritation persists, seek prompt medical attention.
- Ingestion** : Call a physician or Poison Control Centre immediately. Do NOT induce vomiting. Guard against aspiration into lungs by having the individual turn on their left side.
- Notes For Physician** : Treat symptomatically.

**SECTION 5 - FIRE FIGHTING MEASURES**

**Fire hazards/conditions of flammability**

: Not flammable under normal conditions of handling. This product will not burn, due to its water content.

**Flammability classification (OSHA 29 CFR 1910.1200)**

: OSHA Combustible Liquid IIIB.

**Flash point**

: Not available.

**Flash point Method**

: Not applicable.

**Auto-ignition temperature**

: Not available.

**Lower flammable limit (% by vol.)**

: Not applicable.

**Upper flammable limit (% by vol.)**

: Not applicable.

**Suitable extinguishing media**

: Dry chemical, foam, carbon dioxide and water fog.

**Explosion data: Sensitivity to mechanical impact / static discharge**

: Not expected to be sensitive to mechanical impact or static discharge.

**Special fire-fighting procedures/equipment**

: Firefighters should wear an approved full-face, self-contained breathing apparatus (SCBA) and impervious clothing. Water may be ineffective on fire, but may be helpful in cooling unburned containers. Do not use a solid water stream as it may scatter and spread fire. If water is used, fog nozzles are preferable.

**Hazardous combustion products**

: Oxides of carbon, nitrogen, and sulphur. Oxygen. Acrid fumes, toxic gases.

**Oxidizing properties**

: None reported by the manufacturer.



**FLUORESCENT PAINT**

MSDS No.:5770, 5780 Series

MSDS Preparation Date: April 1, 2012

Page 3 of 12

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

- Personal precautions** : All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Avoid breathing vapors. Wear resistant clothing and boots.
- Environmental precautions** : Prevent product from entering drains, sewers, waterways and soil.
- Spill response/cleanup** : Eliminate all ignition sources if safe to do so. Ventilate area of release. Use only non-sparking tools and equipment in the clean-up process. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13).
- Containment** : Should not be released into the environment. Recover free liquid or cover with inert absorbent material and place into appropriate container for disposal.

**SECTION 7 - HANDLING AND STORAGE**

- Safe Handling procedures** : Use with adequate ventilation. Avoid breathing vapor or mist. Avoid contact with skin and eyes. Wash hands thoroughly after using this product, and before eating, drinking or smoking. Avoid breathing of dust created by cutting, sanding, or grinding. Sanding and grinding dusts may be harmful if inhaled. Do not re-use empty containers. Do not puncture container. Keep in properly labeled containers. Containers should be grounded when pouring. Wear suitable protective equipment. Do not ingest. Keep out of direct sunlight.
- Storage requirements** : Store in a cool, dry, well-ventilated area. Keep away from excessive heat, open flames, sparks and other possible sources of ignition. Do not freeze. Keep container tightly closed when not in use. Store in upright position only. Keep out of the reach of children. Empty product containers may contain hazardous product residue. Store out of direct sunlight.
- Incompatible materials** : Oxidizing agents. Acids and bases. Aluminum. Ammonium salts. Other: magnesium, chlorinated rubber.
- Special packaging materials** : Liquid-proof glass, plastic or non-corrodible metal containers are recommended.

**SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION**

- Ventilation and engineering measures** : Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Use explosion-proof equipment. Discharge exhaust only in area away from ignition sources.
- Respiratory protection** : Use NIOSH/MSHA approved full-face respirator with an organic vapor cartridge if the recommended exposure limit is exceeded. In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.
- Skin protection** : Wear impervious gloves, such as neoprene or nitrile rubber.
- Eye / face protection** : Safety glasses with side-shields or chemical splash goggles.
- Other protective equipment** : Emergency showers and eyewash facilities should be nearby. Depending on conditions of use, safety shoes and additional protective clothing may also be necessary.
- General hygiene considerations** : Wash hands thoroughly after using this product, and before eating, drinking or smoking. Wash hands before breaks and at the end of workday.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

- Physical state** : Liquid.
- Appearance** : Clear liquid.  
Milky, white liquid. (Invisible Blue, No. 5785)
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not available.



FLUORESCENT PAINT

MSDS No.:5770, 5780 Series

MSDS Preparation Date: April 1, 2012

Page 4 of 12

Boiling point : 100 °C
Melting/Freezing point : Not available.

Specific gravity : 1.0 - 1.3

Coefficient of water/oil distribution

: Not available.

Vapor pressure (mmHg @ 20° C / 68° F) : 1.0 - 760

Solubility in water : soluble

Vapor density (Air = 1) : Heavier than air.

Evaporation rate (n-Butyl acetate = 1)

: Slower than n-butyl acetate

Volatile organic Compounds (VOC's) (lbs/gal;g/l) : 0.46 / 55.48 (No.5779)
0.68 / 82.18 (No.5780)
0.76 / 91.92 (No.5782)
0.68 / 82.07 (No.5783)
0.70 / 84.34 (No.5784)
0.69 / 83.61 (No.5785)
0.61 / 73.87 (No.5786)
0.68 / 81.97 (No.5787)

Volatiles (% by weight) : 49.19 (No. 5779)
48.13 (No. 5780, 5782-5784)
71.2 (No. 5785)
71.8 (No. 5786, 5787)

Viscosity : Not available.

Special Remarks On Fire Hazards

: Not flammable under normal conditions of use. This product will not burn, due to its water content. May spatter if the temperature exceeds the boiling point. Vapors may irritate eyes. May irritate skin.

SECTION 10 - REACTIVITY AND STABILITY DATA

Stability and reactivity : Stable under normal conditions.

Hazardous polymerization : Will not occur.

Conditions to avoid : High temperatures. Keep away from excessive heat, open flames, sparks and other possible sources of ignition. Oxidizing agents. Do not freeze.

Materials To Avoid And Incompatibility

: See Section 7 (Handling and Storage) section for further details.

Hazardous decomposition products

: See hazardous combustion products.

SECTION 11 - TOXICOLOGICAL INFORMATION

Table with 4 columns: Ingredients, LC50(4hr) inh, rat, LD50 oral, LD50 dermal. Values are N/Av for all categories.

Toxicological data : Low order of toxicity for normal industrial handling.

Carcinogenic status : No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive effects : Not expected to have other reproductive effects.

Teratogenicity : Not expected to be a teratogen.

Mutagenicity : Not expected to be mutagenic in humans.

Reproductive Effects : Not expected to have other reproductive effects.

Irritancy : Irritating to eyes, respiratory system and skin.

Sensitization to material : Not expected to be a sensitizer.

Synergistic materials : None reported by the manufacturer.

SECTION 12 - ECOLOGICAL INFORMATION

Environmental effects : None known or reported by the manufacturer.

Important environmental characteristics

: None known or reported by the manufacturer.

Ecotoxicological : No data is available on the product itself.



**FLUORESCENT PAINT**

MSDS No.:5770, 5780 Series

MSDS Preparation Date: April 1, 2012

Page 5 of 12

**SECTION 13 - DISPOSAL CONSIDERATIONS**

- Handling for Disposal** : See Section 7 (Handling and Storage) section for further details.  
**Methods of Disposal** : Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules. Do not puncture or incinerate. Contact waste disposal services.

**SECTION 14 - TRANSPORTATION INFORMATION**

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	None	Not regulated.	Not regulated	-None-	
<b>TDG Additional information</b>	None.				
49CFR/DOT	None	Not regulated.	Not regulated	-None-	
<b>49CFR/DOT Additional information</b>	None.				
ICAO/IATA	None	Not regulated.	Not regulated	-None-	
<b>ICAO/IATA Additional information</b>	None.				
IMDG	None	Not regulated.	Not regulated	-None-	
<b>IMDG Additional information</b>	None.				

**SECTION 15 - REGULATORY INFORMATION**

**US Federal Information:**

All ingredients are listed on the TSCA Inventory, or are exempted materials.  
 SARA Section 313: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical Constituents above de minimus concentrations.

**US State Right to Know Laws:**

California Proposition 65: To the best of our knowledge, this product does not contain any chemicals known to the State of California to cause cancer or reproductive harm.

**Canadian Regulations:**

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

Canadian WHMIS Classification: D2B.

***This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.***



**FLUORESCENT PAINT**



MSDS No.:5770, 5780 Series

**MSDS Preparation Date:** April 1, 2012

Page 6 of 12

**SECTION 16 - OTHER INFORMATION**

- Legend** :
- ACGIH: American Conference of Governmental Industrial Hygienists
  - IARC: International Agency for Research on Cancer
  - N/Ap: not applicable
  - N/Av: not available
  - NIOSH: National Institute of Occupational Safety and Health
  - NTP: National Toxicology Program
  - OSHA: Occupational Safety and Health Administration
- References** :
- Information obtained from sources including original supplier's Material Safety Data Sheet, and references including RTECS and CCOHS Cheminfo.

<p><b>Prepared for:</b> Rosco Laboratories Inc. 52 Harbor View Avenue Stamford, CT, USA, 06902 Phone: (203) 708 8900  <a href="http://http://www.rosco.com/">http://http://www.rosco.com/</a></p>	
<p><b>Prepared by:</b> ICC The Compliance Center Inc. Canada: 1-888-977-4834 USA: 1-888-442-9628  <a href="http://www.thecompliancecenter.com">http://www.thecompliancecenter.com</a></p>	

**DISCLAIMER OF LIABILITY**

Every effort has been made to ensure that the safety information on this sheet is accurate, but because Rosco Laboratories, Inc. has no control over the conditions under which the product will be used, liability is limited exclusively to replacement or refund of the purchase price of this product. Except as stated herein, there are no express or implied warranties, including implied warranties of merchantability or fitness for a particular purpose. Rosco Laboratories, Inc. assumes no liability for injury or incidental or consequential damages arising out of storage, handling or use of this product.

**Preparation Date:** January 3, 2007



**FLUORESCENT PAINT**

MSDS No.:5781

MSDS Preparation Date: April 1, 2012

Page 7 of 12

## MATERIAL SAFETY DATA SHEET

### SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

**Product Name** : **FLUORESCENT PAINT**

Fluorescent Paint - Orange

**Product Use** : Paint

**Chemical Family** : Mixture

**Supplier's name and address:**

**Rosco Laboratories Inc.**

52 Harbor View Avenue  
 Stamford, CT, United States  
 06902

**24 Hr. Emergency Tel #** : (800) 424-9300

**HMIS Rating** : \* - Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

*Health:* \* 2      *Flammability:* 0      *Reactivity:* 0

**WHMIS Classes:**



TOXIC

### SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredients</u>	<u>CAS #</u>	<u>% (weight)</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
			<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Formaldehyde	50-00-0	0.1 - 1.0	N/Av	N/Av	N/Av	N/Av

### SECTION 3 - HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

Clear liquid. Pungent odor. Causes skin and eye irritation. Harmful if inhaled or swallowed Possible sensitizer. Contains material which can cause cancer.

#### \*\*\*POTENTIAL HEALTH EFFECTS\*\*\*

**Target organs** : None reported by the manufacturer.

**Routes of exposure** : *Inhalation:* YES    *Skin Absorption:* YES    *Skin & Eyes:* YES    *Ingestion:* YES

**Potential acute health effects** :

*Eyes:* Causes eye irritation. Prolonged or repeated exposure may be harmful to health. May cause conjunctivitis, irritation, and inflammation of mucous membranes. May cause burning sensation, redness and tearing (watering). Possible severe irritation. Contains materials corrosive or severely irritating to the eyes. Temporary vision impairment (cloudy or blurred vision) is possible. Severe irritation, tissue damage, and possible blindness will result from direct contact.

*Skin:* Irritating to skin. May cause mild to moderate skin irritation. Prolonged or repeated exposure may be harmful to health. Possible irritation, defatting or dermatitis (rash). Components of the product may be absorbed into the body through the skin. May cause central nervous system depression.





**FLUORESCENT PAINT**

MSDS No.:5781

MSDS Preparation Date: April 1, 2012

Page 8 of 12

*Inhalation:* May cause irritation to upper respiratory system. Prolonged exposure to vapors may be harmful to health. If higher concentrations are inhaled, additional symptoms may include coughing, shortness of breath, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. May cause mucous membrane irritation. Other adverse effects : Asphyxia. Severe lung irritation or lung damage, loss of appetite. Sanding and grinding dusts may be harmful if inhaled. Contains particles which may cause lung damage if inhaled in large quantities.

*Ingestion:* Lung aspiration hazard. This product may be aspirated (inhaled) into the lungs during ingestion. May cause lung inflammation. May cause mucous membrane irritation. Ingestion may cause symptoms similar to inhalation. May cause gastrointestinal irritation. Gastrointestinal irritation may include abdominal pain, nausea, diarrhea and vomiting. Other adverse effects : intoxication, acidosis. Possible chemical burns to the mouth, throat and upper gastrointestinal tract. May cause liver and kidney damage.

**Potential chronic health effects**

: Prolonged skin contact may defat the skin and produce dermatitis. Harmful by skin absorption. May cause central nervous system depression. Prolonged inhalation of vapors may cause lung damage, including chronic bronchitis. Prolonged exposure may result in neurological dysfunction. May cause skin sensitization. Contact dermatitis can result from prolonged overexposure. Allergic respiratory reactions to these materials are characterized by asthma-like symptoms such as chest tightness, wheezing, shortness of breath and coughing.

**Medical conditions aggravated by overexposure**

: None expected, when used as intended.

**Additional health hazards**

: Formaldehyde is a potential cancer hazard, a skin sensitizer and a respiratory sensitizer.

**Potential environmental effects**

: None reported by the manufacturer.

**SECTION 4 - FIRST AID MEASURES**

**Inhalation** : If breathed in, move person into fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Seek immediate medical attention/advice.

**Skin contact** : Flush with plenty of water. Wash off with soap and plenty of water. Remove and wash contaminated clothing before re-use. If irritation persists, seek prompt medical attention.

**Eye contact** : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If irritation persists, seek prompt medical attention.

**Ingestion** : Call a physician or Poison Control Centre immediately. Do NOT induce vomiting. Guard against aspiration into lungs by having the individual turn on their left side.

**Notes For Physician** : Treat symptomatically.

**SECTION 5 - FIRE FIGHTING MEASURES**

**Fire hazards/conditions of flammability**

: Not flammable under normal conditions of handling. This product will not burn, due to its water content.

**Flammability classification (OSHA 29 CFR 1910.1200)**

: OSHA Combustible Liquid IIIB.

**Flash point**

: Not available.

**Flash point Method**

: Not applicable.

**Auto-ignition temperature** : Not available.

**Lower flammable limit (% by vol.)**

: Not applicable.

**Upper flammable limit (% by vol.)**

: Not applicable.

**Suitable extinguishing media**

: Dry chemical, foam, carbon dioxide and water fog.

**Explosion data: Sensitivity to mechanical impact / static discharge**

: Not expected to be sensitive to mechanical impact or static discharge.

**Special fire-fighting procedures/equipment**

: Firefighters should wear an approved full-face, self-contained breathing apparatus (SCBA) and impervious clothing. Water may be ineffective on fire, but may be helpful in cooling unburned containers. Do not use a solid water stream as it may scatter and spread fire. If water is used, fog nozzles are preferable.





**FLUORESCENT PAINT**

MSDS No.:5781

MSDS Preparation Date: April 1, 2012

Page 9 of 12

**Hazardous combustion products**

: Oxides of carbon, nitrogen, and sulphur. Oxygen. Acrid fumes, toxic gases.

**Oxidizing properties**

: None reported by the manufacturer.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

**Personal precautions**

: All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Avoid breathing vapors. Wear resistant clothing and boots.

**Environmental precautions**

: Prevent product from entering drains, sewers, waterways and soil.

**Spill response/cleanup**

: Eliminate all ignition sources if safe to do so. Ventilate area of release. Use only non-sparking tools and equipment in the clean-up process. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13).

**Containment**

: Should not be released into the environment. Recover free liquid or cover with inert absorbent material and place into appropriate container for disposal.

**SECTION 7 - HANDLING AND STORAGE**

**Safe Handling procedures**

: Use with adequate ventilation. Avoid breathing vapor or mist. Avoid contact with skin and eyes. Wash hands thoroughly after using this product, and before eating, drinking or smoking. Avoid breathing of dust created by cutting, sanding, or grinding. Sanding and grinding dusts may be harmful if inhaled. Do not re-use empty containers. Do not puncture container. Keep in properly labeled containers. Wear suitable protective equipment. Do not ingest. Keep out of direct sunlight.

**Storage requirements**

: Store in a cool, dry, well-ventilated area. Keep away from excessive heat, open flames, sparks and other possible sources of ignition. Do not freeze. Keep container tightly closed when not in use. Store in upright position only. Keep out of the reach of children. Empty product containers may contain hazardous product residue. Store out of direct sunlight.

**Incompatible materials**

: Oxidizing agents. Acids and bases. Aluminum. Ammonium salts. Other: magnesium, chlorinated rubber.

**Special packaging materials**

: Liquid-proof glass, plastic or non-corrodible metal containers are recommended.

**SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION**

**Ventilation and engineering measures**

: Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Use explosion-proof equipment. Use non-sparking equipment. Discharge exhaust only in area away from ignition sources.

**Respiratory protection**

: Use NIOSH/MSHA approved full-face respirator with an organic vapor cartridge if the recommended exposure limit is exceeded. In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

**Skin protection**

: Gloves impervious to the material are recommended.

**Eye / face protection**

: Safety glasses with side-shields or chemical splash goggles.

**Other protective equipment**

: Emergency showers and eyewash facilities should be nearby. Depending on conditions of use, safety shoes and additional protective clothing may also be necessary.

**General hygiene considerations**

: Wash hands thoroughly after using this product, and before eating, drinking or smoking. Wash hands before breaks and at the end of workday.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

**Physical state**

: Liquid.

**Appearance**

: Clear liquid.

**Odor**

: Sharp, penetrating odor.

**Odor threshold**

: Not available.



**FLUORESCENT PAINT**

MSDS No.:5781

MSDS Preparation Date: April 1, 2012

Page 10 of 12

pH : Not available.  
 Boiling point : -19.39 °C  
 Melting/Freezing point : Not available.  
 Vapor pressure (mmHg @ 20° C / 68° F) : 1.0 - 760  
 Vapor density (Air = 1) : Heavier than air.  
 Volatile organic Compounds (VOC's) (lbs/gal;g/l) : 0.72 / 86.25  
 Viscosity : Not available.  
 Specific gravity : 1.07  
 Coefficient of water/oil distribution : Not available.  
 Solubility in water : Soluble  
 Evaporation rate (n-Butyl acetate = 1) : Slower than n-butyl acetate  
 Volatiles (% by weight) : 71.6  
 Special Remarks On Fire Hazards : Not flammable under normal conditions of use. This product will not burn, due to its water content. May spatter if the temperature exceeds the boiling point. Vapors may irritate eyes. May irritate skin.

**SECTION 10 - REACTIVITY AND STABILITY DATA**

Stability and reactivity : Stable under normal conditions.  
 Hazardous polymerization : Will not occur.  
 Conditions to avoid : High temperatures. Keep away from excessive heat, open flames, sparks and other possible sources of ignition. Oxidizing agents. Do not freeze.  
 Materials To Avoid And Incompatibility : See Section 7 (Handling and Storage) section for further details.  
 Hazardous decomposition products : See hazardous combustion products.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

<u>Ingredients</u>	<u>LC<sub>50</sub>(4hr)</u> <u>inh, rat</u>	<u>LD<sub>50</sub></u>	
		<u>oral</u>	<u>dermal</u>
Formaldehyde	308 mg/m <sup>3</sup> /2H (rat), 250 ppm/2H (rat)	100 mg/kg (rat)	300 mg/kg (rabbit)

Toxicological data : Low order of toxicity for normal industrial handling.  
 Carcinogenic status : Contains the following chemical(s) classified as ACGIH Group A2 (suspected human carcinogen): formaldehyde.  
 Contains the following chemical(s) listed as Group I (Human Carcinogens) by IARC: formaldehyde.  
 Contains the following chemical(s) listed as an Anticipated Carcinogen by NTP: formaldehyde.  
 Contains the following chemical(s) listed as a carcinogen by OSHA: formaldehyde.  
 Reproductive effects : Not expected to have other reproductive effects.  
 Teratogenicity : Not expected to be a teratogen.  
 Mutagenicity : Contains a chemical or chemicals that may be mutagens. This product contains: formaldehyde.  
 Reproductive Effects : Not expected to have other reproductive effects.  
 Irritancy : Eyes, skin, respiratory system and digestive system. Formaldehyde is an eye and throat irritant and acute toxicant.  
 Sensitization to material : Skin and/or respiratory sensitizer.  
 Synergistic materials : The product contains an ingredient which may enhance the effect of other carcinogens. This product contains: formaldehyde.  
 Components of the product may affect the nervous system.

**SECTION 12 - ECOLOGICAL INFORMATION**

Environmental effects : None known or reported by the manufacturer.



**FLUORESCENT PAINT**

MSDS No.:5781

**MSDS Preparation Date:** April 1, 2012

Page 11 of 12

**Important environmental characteristics**

: None known or reported by the manufacturer.

**Ecotoxicological**

: No data is available on the product itself.

**SECTION 13 - DISPOSAL CONSIDERATIONS**

**Handling for Disposal**

: See Section 7 (Handling and Storage) section for further details.

**Methods of Disposal**

: Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules. Do not puncture or incinerate. Contact waste disposal services.

**SECTION 14 - TRANSPORTATION INFORMATION**

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	None	Not regulated.	Not regulated	-None-	
<b>TDG Additional information</b>	None.				
49CFR/DOT	None	Not regulated.	Not regulated	-None-	
<b>49CFR/DOT Additional information</b>	None.				
ICAO/IATA	None	Not regulated.	Not regulated	-None-	
<b>ICAO/IATA Additional information</b>	None.				
IMDG	None	Not regulated.	Not regulated	-None-	
<b>IMDG Additional information</b>	None.				

**SECTION 15 - REGULATORY INFORMATION**

**US Federal Information:**

All ingredients are listed on the TSCA Inventory, or are exempted materials.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This product may be subject to SARA notification requirements, since it contains Toxic Chemical constituents above their de minimus concentrations. This product contains: formaldehyde.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): formaldehyde: 100 lb, 45.4 kg.

**US State Right to Know Laws:**

California Proposition 65: This product contains a chemical known to the State of California to cause cancer and/or reproductive harm. This product contains: formaldehyde.

**Canadian Regulations:**

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

Canadian WHMIS Classification: D2A, D2B.



**FLUORESCENT PAINT**

MSDS No.:5781



MSDS Preparation Date: April 1, 2012

Page 12 of 12

*This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.*

**SECTION 16 - OTHER INFORMATION**

- Legend** : ACGIH: American Conference of Governmental Industrial Hygienists  
IARC: International Agency for Research on Cancer  
N/Ap: not applicable  
N/Av: not available  
NIOSH: National Institute of Occupational Safety and Health  
NTP: National Toxicology Program  
OSHA: Occupational Safety and Health Administration
- References** : Information obtained from sources including original supplier's Material Safety Data Sheet, and references including RTECS and CCOHS Cheminfo.

<p><b>Prepared for:</b>  Rosco Laboratories Inc.  52 Harbor View Avenue  Stamford, CT, USA, 06902  Phone: (203) 708 8900   <a href="http://http://www.rosco.com/">http://http://www.rosco.com/</a></p>	
<p><b>Prepared by:</b>  ICC The Compliance Center Inc.  Canada: 1-888-977-4834  USA: 1-888-442-9628   <a href="http://www.thecompliancecenter.com">http://www.thecompliancecenter.com</a></p>	

**DISCLAIMER OF LIABILITY**

Every effort has been made to ensure that the safety information on this sheet is accurate, but because Rosco Laboratories, Inc. has no control over the conditions under which the product will be used, liability is limited exclusively to replacement or refund of the purchase price of this product. Except as stated herein, there are no express or implied warranties, including implied warranties of merchantability or fitness for a particular purpose. Rosco Laboratories, Inc. assumes no liability for injury or incidental or consequential damages arising out of storage, handling or use of this product.

Preparation Date: January 3, 2007

**END OF DOCUMENT**