

# Specifications

## SOURCE

250W RGBWAL (Red/Green/Blue/White/Amber/Lime) LED Engine

50,000 Hour Average LED Life\*

\*LED Life may vary depending on several factors including but not limited to:

Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming.

## PHOTOMETRIC DATA

>90CRI 6,000 Total Lumens\*

(\*with 26° lens)

## EFFECTS

Electronic Strobe and Dimming

Variable Dimming Curves and Dimming Modes

## GOBOS

Supports “B” Size Metal, HT Transparency Gobos\*

\*Gobos and Holder not included.

## CONTROL / CONNECTIONS

(3) DMX Channel Modes (6 / 9 / 12)

Adjustable Refresh Rate (900-1500, 25,000 Hz)

4 Button Control Panel

LED Menu Display

Locking 5pin XLR Connector In/Out

Locking Power Connector In/Out

With Wired Digital Communication Network

## SIZE / WEIGHT

Length: 27.1” (688mm) (Lens In)

Width: 111.3” (287mm)

Vertical Height: 17.7” (450mm)

Weight: 20.0 lbs. (9.1 kg)

## ELECTRICAL / THERMAL

Quiet Fan Cooling

AC 100-240V - 47/63Hz

250W Max Power Consumption

Power Linking: 3pcs Max @120V / 8pcs Max @240V

14° to 113°F (-10° to 45°C)

## APPROVALS / RATINGS

CE | cETLus (Pending) | IP30

## INCLUDED ITEMS

(1) Locking Power Cable

## OPTIONAL ACCESSORIES:

EP Lens 5 (5° Lens)

EP Lens 10 (10° Lens)

EP Lens 14 (14° Lens)

EP Lens 19 (19° Lens)

EP Lens 26 (26° Lens)

EP Lens 36 (36° Lens)

EP Lens 50 (50° Lens)

EP Lens 15-30 (Adjustable 15° to 30° Lens Assembly)

EP Lens 25-50 (Adjustable 25° to 50° Lens Assembly)

Specifications and documentation subject to change without notice.