

High Output, RGBALC Color Mixing

Exceptional Quality

The HotBox™ X4 RGBALC is a top performer and undoubtedly our most powerful and versatile HotBox™ to date. Equipped with 4x 20W RGBALC 6-in-1 LEDs, it delivers vibrant color mixing and smooth effects. It can be rigged for stage lighting, used in a freestanding position, or easily fit into standard-sized box trusses for truss warming. With a 25° beam angle, variable dimming curves, and striking strobe effects, it is perfect for a wide range of indoor lighting applications.



Built with advanced features and durability in mind, this fixture offers multiple built-in programs, customizable chase effects, and is ideal for video applications with flicker-free LEDs and useradjustable PWM settings. Its well-structured 4-button OLED menu ensures easy navigation, while RDM protocol adds another layer of professional control. Housed in a solid metal casing, it features industry-standard powerCON® TRUE1-compatible power and 5-pin DMX in/out connections.

Luminous Intensity

Beam	2M	2.5M	3M	4M	5M
 25° ,	5,563	3,059	2,379	1,319	820



Main Features

- 4x 20W RGBALC 6-in-1 LEDs, 100,000 hrs.
- RGBALC color mixing ability in standalone mode
- Built-in color & chase macros via DMX
- Built-in automated programs via master/slave
- Virtual color wheel
- 6/8/12-channel DMX profiles w/32-bit dimming
- Flicker-free constant-current LED driver
- 25 degree beam angle
- Easy-to-use, 4-button OLED control menu
- Dual mounting brackets for positioning flexibility
- 5-pin male/female XLR input & output connections
- PowerCON® TRUE1™ compatible in/out power connectors



Optical

4x 20W RGBALC 6-in-1 LEDs (100,000 hours)

Flicker-free LEDs

25° beam angle



Weight & Dimensions

x 119.2 x 183.2 mm)

4.25 lbs (1.94 kg)

8.1" x 4.7" x 7.2" (205.5 Protocol: USITT DMX-512,

6/8/12-channel DMX

4-button menu with **OLED** display

[444]

Control

RDM

5-pin DMX in/out

DMX512, M/S, auto mode



Power + Current

100-240VAC, 50-60 Hz

Consumption: 67W, 0.95A, PF: .6

PowerCON® TRUE1compatible in/out



Warranty + Certifications

2-year limited warranty













